



SAFETY TREAD

Installation of Stair Inserts

1. Ensure that the stair surface/rebate area is level and flat.
2. Select the most suitable cartridge adhesive for interior/exterior usage.
3. Ensure stairs are clean and free of debris, dust, grease and oil.
4. Check the stair is dry and free from dampness.
5. Apply adhesive to underside of insert and place into rebate.
6. The insert needs to sit flush with the surface to avoid potential trips.
7. Please allow the adhesive to cure for the recommended time.

Tips : Do not rebate until receipt of your order to allow for standard Manufacturing Tolerance's.

Maintenance

To ensure that effective slip-resistance and optimum step edge definition is maintained, tread inserts and riser strips must be cleaned at least weekly.

Composition PVC inserts require particular scrubbing as the nature of the material is more easily marked than say, carborundum. The mechanically abraded surfaces of PVC inserts, which is necessary for providing slip-resistance, also readily retains dirt. For minimal maintenance, carborundum inserts are recommended.

For best results, scrub with a solution of propriety floor cleaner and warm water. Difficult to remove marks may require extra scrubbing using a cream cleaner or similar.

After cleaning, remove any excess water and allow the nosings / treads to fully dry before allowing pedestrian access.

If the aluminium profile requires buffing, the best results are achieved by using a fine grade (000 gauge) wire wool.

Tips : DO NOT USE WAXES OR POLISHING MEDIA THAT MAY COMPROMISE SLIP- RESISTANCE

Warranties

All Safetytread products are covered by one or more of the following warranties, providing that –

- a. The product used is appropriate for the application.
- b. The product used has been installed and maintained in accordance with our instructions.

Carborundum – filled profiles are guaranteed against premature wear for a period of 10-years following the date of installation

PVC Composition – filled profiles are guaranteed against premature wear for a period of 2-years following the date of installation

Abrazel Tape – profiles are not warrantied against premature wear

In the event of premature wear or other product failure being proven, our guarantee extends only to the free replacement of the product. No claim will be entertained in respect of any other costs incurred effecting a satisfactory re-installation of the site(s).